

Steel Frame Assembly: XDrive® Framer

APPLICATION



- Assembly of steel frame walls, joists and trusses.
- Sharp Point: For pre-punched, TCT 0.75 – 0.95 mm steel (22 – 20 gauge)
- Drill Point: For pre-punched as well as non-punched, TCT 0.95 to 1.55 mm steel (20–16 gauge)

FEATURES AND BENEFITS

- Sharp Point aligns pre-punched holes during frame assembly for a high quality accurate finish.
- Drill Point is designed for easy penetration into heavier gauge steel for quick and easy assembly.
- XDrive® recess delivers increased stability and higher torque making it significantly easier to drive, reducing worker fatigue and increasing productivity.
- XDrive® incorporates a larger surface area of engagement, reducing stress on driver bits resulting in fewer breakages.
- Low profile flat head sits perfectly flush with the steel frame edge, providing a smooth, flat finishing surface for easy and accurate installation of cladding and lining.
- Under head serrations slow the rotation of the head to reduce the possibility of strip out, they also provide pressure under head to reduce vibrational loosening during transportation.
- E-Coat offers a high level of corrosion resistance and durability.
- Compatible with Superdrive® collated screw system to increase the efficiency in frame assembly.

SPECIFICATIONS

- Coating: FRAMECAD® E-Coat: SST: 1000hrs in accordance with ASTM B117
FRAMECAD® E-Coat: AS3566.2 2002: Class 3
- Installation: RPM 1,800 - 2,500
- Compliance: ISO 9001
ISO14001

Product	Order Code	Size	Description	Carton Qty
XDrive® Framer SP 	Ideal for use in all industrial, commercial, and residential projects. Suitable for pre-punched steel frames up to 0.95mm thick.			
	001236	10g x 19mm	XDrive Framer SP, 1000hrs, Loose	8,000
	002962 **	10g x 19mm	XDrive Framer SP, 1000hrs, Collated	4,000
XDrive® Framer DP 	Ideal for use in all industrial, commercial, and residential projects. Suitable for steel frames between 0.95mm and 1.95mm thick.			
	001877	10g x 19mm	XDrive Framer DP, 1000hrs, Loose	8,000
	002964 **	10g x 19mm	XDrive Framer DP, 1000hrs, Collated	4,000
	002965	12g x 19mm	XDrive Framer DP, 1000hrs, Loose	6,000
	002966 **	12g x 19mm	XDrive Framer DP, 1000hrs, Collated	4,000

‘**’ indicates a supply lead time may be applicable.

Unmarked items may be in stock at FRAMECAD warehouse near you. Please contact your account manager for info.